
Submittal Data and Specifications

Flexible PVC Reducers / Couplings

Material of Construction and Temperature Limitations:

Body shall be made of flexible PVC. Compression Clamps shall be made of stainless steel. Recommended up to 140° F.

Application:

Designed to operate in highly corrosive environments. Provides coupling and transition from ducting to fan inlet and outlet.

Shall have the following Features and Benefits:

- Flexible PVC provides excellent connection between fan and ducting
- Corrosive resistant construction materials
- Stretch/Compression Factor of 5% allows snug fit to prevent leaks
- Excellent transition models available for ease of installation
- Provides effective vibration isolation between duct and fan

Warranty:

This equipment is warranted to be free from defects in material and workmanship for two years from date of original shipment.



PROJECT			ARCHITECT	
CONTRACTOR	DATE	SUBMITTED BY		ENGINEER
SPECIFICATION				
RELATED FAN POSITION	MODEL #	QTY	NOTES	

Submittal Data and Specifications

Flexible PVC Reducers / Couplings

DIMENSIONAL DATA REPORT							
Plastec Part #	Inside Dimension In Inches		Height In Inches	Plastec Part #	Inside Dimension In Inches		Height In Inches
	A	B	C		A	B	C
101-44	5.30	5.30	4.00	156-53	5.50	3.40	5.00
102-44	5.30	4.40	4.00	156-54	5.50	4.40	5.00
102-46	5.30	6.40	6.00	156-63	6.40	3.40	6.00
102-88	7.50	8.55	6.00	156-64	6.40	4.40	6.00
102-1210	14.50	10.60	6.50	156-66	6.40	6.40	6.00
104-86	10.25	7.80	6.00	156-86	8.55	6.40	6.00
106-66	7.80	6.40	6.00	156-88	8.55	8.55	6.00
156-33	3.40	3.40	4.00	156-108	10.60	8.55	6.50
156-33C	3.40	2.90	4.00	156-128	12.60	10.60	6.50
156-43	4.40	3.40	4.00	156-1010	10.60	10.60	6.50
156-43C	4.40	3.90	4.00	156-1210	12.60	10.60	6.50
156-44	4.40	4.40	5.00	156-1212	12.60	12.60	6.50

